

K-Type Thermocouple Thermometer

Item # TC-9212 A / B



0519211 מ"ק"ט

K-Type Thermocouple Probe

Part No.: 93S Z001-K64225S K01

FEATURES:

- One hour auto shut off
- 1 second normal temperature sensing time
- Low battery indicator
- PVC holster with flip-out stand at the back of unit
- Battery : 3 x 1.5 Volts "AAA" or equivalent

MEASUREMENT RANGE

- $-200^{\circ}\text{C} \sim +1370^{\circ}\text{C}$ or $-328^{\circ}\text{F} \sim +2498^{\circ}\text{F}$

RESOLUTION:

- 0.1° for $-199.9^{\circ} \sim +1369.9^{\circ}$

ACCURACY:

- $\pm 2^{\circ}\text{C}$ from $-200^{\circ}\text{C} \sim -50^{\circ}\text{C}$ (or 4°F from $-328^{\circ}\text{F} \sim -58^{\circ}\text{F}$)
- $\pm 1^{\circ}\text{C}$ from $-49^{\circ}\text{C} \sim +740^{\circ}\text{C}$ (or 1.8°F from $-56.2^{\circ}\text{F} \sim +1364^{\circ}\text{F}$)
- $\pm 2^{\circ}\text{C}$ from $+741^{\circ}\text{C} \sim +1300^{\circ}\text{C}$ (or 4°F from $+1365.8^{\circ}\text{F} \sim +2372^{\circ}\text{F}$), otherwise more than 2°C or 4°F .
- Accuracy is specified for operating temperatures over the range of 18°C to 28°C (64°F to 82°F). The basic accuracy specification does not include the error of the thermocouple probe.

AMBIENT TEMPERATURE FOR PLASTIC CASING:

- $-10^{\circ}\text{C} \sim +50^{\circ}\text{C}$ (or $+14^{\circ}\text{F} \sim +122^{\circ}\text{F}$)